

1. identification

- A. Product name
- Ethanol 95%
- B. Recommended use and restriction on use
- O Recommended Use: Industrial use (Synthetic detergent, Organic synthesis resins, Inks, Dyes, Cleaning

agent, Reagents, toilet soap, toilet water perfume, paint diluent, adhesive),

Category 2

(Flash Point $< 23^{\circ}$ C, Boiling point $> 35^{\circ}$ C)

Category 2 (Skin Irritant material) Category 1A (in Alcoholic beverage)

medicine(antiseptic), Cosmetic

- O Restrictions on Use: Restrict except for recommended use
- C. Manufacturer / Supplier / Distributor information
- O Supplier information

- Supplier : GODO CHEMICAL Corporation

- Address: #1017, 10F Suseo Hyundai Ventureville 10 Bamgogae-ro 1-gil Gangnam-gu Seoul

06349 Korea

Telephone: (82)2 417 2555~6Email: godochem@godochem.com

2. hazard identification

A. Classification

Flammable Liquid

Serious eye damage or iritant material

Carcinogenicity

B. Warning

O Label







- O Hazard Communication: DANGER!
- O Label Element

H225 Highly flammable Liquid and Vapor

H319 Cause eye irritation.

H350 May cause canser (in Alcoholic beverage)

- O Terms for Precaution
 - Precaution

P201	Obtain special instructions before use.
P202	Do not handle until al safety precautions have ben read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P233	Keep container tightly closed.
P240	Ground/Bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/../equipment.

Material Safety Data Sheet

Ethanol 95%



	P242	Use	only	non-sparking tools.	
--	------	-----	------	---------------------	--

P243 Take precautionary measures against static discharge.

P264 Wash hands thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

- Response

P303+P361+P353 If on skin(or hair) Take of immediately al contaminated clothing

Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire, use water spray/alcohol resistant foam for extinction.

Storage

P403+P235 Store in a weel-ventilated place and keep cooling.

P405 Store in lockable storage area.

- Disposal

P501 Dispose of contents/container by incineration or recycle.

C. Other

○ NFPA

Health 1Flammability 3Reactivity 0

3. composition/information on ingredients

Chemical name : Ethanol K95

Synonyms : Ethanol CAS number : 64-17-5

Content(%) :

Name	Trade names and Synonyms	KE No.	Content (vol%)
Ethyl Alcohol	Ethyl alcohol; Ethanol solution; Alcohol; Fermentation alcohol; Algrain; Ethyl hydrate; Ethyl hydroxide	KE-13217	95 vol%

4. first aid measures



A. Eve contact

Do not rub your eyes.

Immediately flush eyes with plenty of water for at least 15 minutes and cal a doctor/physician. Get medical attention immediately.

det medical attention immediat

B. Skin contact

Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.

Laundering enough contaminated clothing before reuse.

Get medical attention immediately.

C. Inhalation contact

When exposed to large amounts of steam and mist, move to fresh air.

Take specific treatment if needed.

Get medical attention immediately.

D. Ingestion contact

Please be advised by doctor whether induction of vomit is demanded or not.

Rinse your mouth with water immediately.

Get medical attention immediately.

E. Notes to physician

Notify medical personnel of contaminated situations and have them take appropriate protective measures.

5. fire fighting measures

A. Suitable(or unsuitable) extinguish media

Dry chemical, carbon dioxide, regular foam extinguishing agent, spray

Avoid use of water jet for extinguishing

Wear fire fighting clothing, fire fighting helmets, fire fighting gear, fire fighting gloves, and respirator when fighting fire.

B. Specific hazards arising from the chemical

Highly flammable liquids and vapors.

Violent polymerization may cause fire and explosion.

Vapors can be transferred to the ignition sources of ignition.

During burning, pyrolysis or combustion can produce irritating and highly toxic gases.

May form explosive mixture at or above flash point.

Containers may explode on heating.

Highly flammable: Easily ignited by heat, sparks and flames.

Leaks may present a fire/explosion hazard.

Vapors are explosive at room, outdoors, and at the sewers.

Vapors may form explosive mixtures with air.

Vapors may travel to the source of ignition and backfire.

Vapors may cause dizziness or suffocation.

Inhalation and contact may irritate or burn the skin and eyes.

C. Special protective actions for fire-fighting



For large fires, use an unmanned waterproofing device, and if not, leave it to burn.

Do nat approach if the tank is covered by a flame.

Find and use appropriate evolutionary methods for your surroundings.

Wear appropriate protective equipment if necessary.

Vapor or gas is burned at distant ignition sources can be spread quickly.

Due to the extremely low flash point, irrigating fire extinguishing may be les effective when put out a fire.

6. additional release measures

A. Personal precautions, protective equipment and emergency procedures

Accidental release wear protection: Chemical resistant protective gloves, goggles, protective face, chemical resistant, respiratory protection.

Ventilate closed spaces before entering.

Do not touch spiled material. Stop leak if you can do it without risk.

Move container to safe area from the leak area.

Remove al sources of ignition.

Do not direct water at spil or source of leak.

Keep unauthorized people away, isolate hazard area and deny entry.

Avoid skin contact and inhalation.

B. Environment precautions

Prevent runoff and contact with waterways, drains or sewers.

If large amounts have ben spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up -

- Large spill: Stay upwind and keep out of low areas. Dike for later disposal.

Notification to central government, local government. When emissions at

least of the standard amount

Dispose of waste in accordance with local regulation.

Appropriate container for disposal of spilled material collected.

- Small leak: sand or other non-combustible material, please let use absorption.

Wipe of the solvent. Dike for later disposal.

Do not use plastic containers.

7. handling and storage

A. Precaution for safe handling

Avoid contact with incompatible materials.

Save applicable laws and regulations.

Refer to Engineering controls and personal protective equipment.

Operators should wear antistatic footwear and clothing.

Do not inhale the vapors prolonged or repeated.

Avoid contact with heat, sparks, flame or other ignition sources.



B. Conditions for safe storage

Do not apply direct heat.

Avoid direct sunlight.

Store in original container only.

Please pay attention to incompatibilities materials and conditions to avoid.

Caution: Flammables.

Please collected in closed containers.

8. exposure controls/personal protection

A. Control parameters - Occupational Exposure Limits

○ Domestic regulation : TWA - 1000ppm 1900mg/m3
 ○ ACGIH : STEL - 1000ppm (1880 mg/m3)

O Biological exposure standard: Not available

B. Engineering Controls

Business owner is recommended to maintain below recommended exposure limits for the working place with general exhaust of gas/vapour/mist/fume.

- C. Personal protection
 - O Respiratory protection

Under conditions of frequent use or heavy exposure, Respiratory protection may be neded.

Respiratory protection is ranked in order from minimum to maximum.

Consider warning properties before use.

Any chemical cartridge respirator with organic vapor cartridge(s).

Any chemical cartridge respirator with a full facepiece and organic vaporcaritridge(s).

Any air-purifying respirator with a full facepiece and an organic vapor canister.

For Unknown Concentration or Immediately Dangerous to Life or Health: Any supplied—air respirator with ful facepiece and operated in a presure—demand or other positive—pressure mode in combination with a separate escape supply. Any self—contained breathing apparatus with a full facepiece.

O Eye protection

Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.

Provide an emergency eye wash station and quick drench shower in the immediate work area.

O Hand protection

Wear appropriate chemical resistant glove.

O Body protection

Wear appropriate chemical resistant protective clothing.



9. physical and chemical properties

C. Odor threshold : 10 ppm

D. pH : 7 (10g/L, H2O, 20°C) **Source : Chemical book

H. Evaporation rateI. Flammable(solid, gas)No data

L. Solubility : $789,00 \text{ mg/l} (20^{\circ}\text{C})$

*Source : ECHA Registered Substances

N. Specific gravity : $0.81639 (15^{\circ}C/15^{\circ}C)$

Q. Decomposition temperature : No data

R. Viscosity : 1.074 cP (20°C, mPa s) **Source : ICSC

S. Molecular formular/Weight : CH3CH2OH / 46.07

10. stability and reactivity

A. Chemical stability & Possibility of hazardous reactions

: This material is stable under recommended storage

and handling conditions.

Hazardous Polymerization will not occur.

B. Conditions to avoid : Avoid contact with incompatible materials and condition.

Avoid contact with heat, sparks, flame or other ignition sources.

C. Incompatible materials : Not availableD. Hazardous decomposition materials : Not available

11. toxicological information

A. Information on the likely routes of exposure

Respiratory tracts Not available Oral contact Not available

O Eye, Skin contact : Cause mild skin irritation.



B. Delayed and immediate effects and also chronic effects from short and long term exposure

O Acute toxicity

- Oral : LD50 = 7,060 mg/kg Rat (OECD Guideline 401)

**Source : ECHA

- Dermal : Not available

- Inhalation : LC50 = 30,300 mg/m3/4hr Mouse (OECD Guideline 403)

*Source : ECHA

O Skin corrosive or Irritation : Skin corrosion/irritation test using rabbit does not

result in irritation. (OECE Guideline 404, GLP)

**Source : ECHA

O Acute eye damages or Irritation: Severe eye injuries/irritation tests using rabbits resulted

in conjunctivitis. conjunctival edema, irs damage, and corneal damage. (Conjunctival index : 2.1, irs index : 0.44, Conjunctival edema index : 1.3, Corneal index : 1.1, OECD Guideline 405)

* Source : ECHA

O Respiratory hypersensitivity : Not available

O Skin hypersensitivity : Skin sensitization test using mouse(female/male)

results in no skin sensitization.

* Source : ECHA

O Carcinogenic : IARC GROUP 1(Ethanol in Alcoholic beverage)

ACGIH A3(Ethanol in Alcoholic beverage)

O Germ cels mutagenicity : The result of domestication test using in vivo rodent.

(OECD Guideline 478) Negative spot test results using in vivo

mouse.(OECD Guideline 484)

Negative results from micronucleus test using in vivo mammalian red blood cells.(OECD Guideline 474)

Negative chromosome aberration test using in vivo mammalian

bone marrow cells.(OECD Guideline 475)

*****Source : ECHA

O Reproductive toxicity : Developmental toxicity/teratogenicity/maternal toxicity test

results using rats have no significant effect. (Developmental toxicity NOAEL = 4000mg/kg,

Teratogenicity NOAEL = 5200mg/kg, Teratogenicity

LOAEL = 8200mg/kg)(OECD Guideline 415)

**Source : ECHA

O Specific target organ toxicity(STOT) - single exposure

Oral toxicity test using rabbit eyes. The vestibular function was inhibited.

*****Source : HSDB

○ Specific target organ toxicity(STOT) - repeated exposure

Repeated oral toxicity tests(98d) with rats showed no significant effect.

**Source: HSDB

O Aspiration hazards : No data C. Numerical measures of toxicity : No data



12. ecological information

A. Aquatic / Terestrial / Ecology toxicity

○ Fish : LC50 > 100 mg/L 96 hr Pimephales promelas

*Source: SIDS 2005

O Shellfish : LC50 5012 mg/l 48 hr Ceriodaphnia dubia

(Other Guideline: ASTM E729-80)

**Source : ECHA

○ Birds : ErC50 275 mg/L 72 hr Chlorela vulgaris

(OECD Guideline 201) *Source : ECHA

B. Persistence and Biodegradability

○ Persistence : -0.32 log Kow **Source : ICSC

O Biodegradability : BOD5 / COD = 0.57 **Source : IUCLID

C. Bioacumulation

O Biodegradability : Biodegradability = 75% 20 day (Aerobic, etc.,

easily decomposed) (IUCLID)

O Bioacumulation : 1 **Source : ECHA

D. Soil mobility: Koc = 1E. Ozone Hazard: No dataF. Other hazardous: No data

13. disposal considerations

A. Method of disposal

Since more than two kinds of designaed waste is mixed, it is difficult to treat seperatly, then can be reduction or stabilization by incineration or similar proces.

If water separation is possible, pre-process with Water separation process.

Dispose by incineration.

B. Caution

The user of this product must disposal by oneself or entrust to waste disposer or person who other's waste recycle and dispose, person who establish and operate waste disposal facilties. Dispose of waste in accordance with all applicable laws and regulations.

14. transport information

A. UN number: 1170

B. UN Shipping name: ETHANOL(ETHYL ALCOHOL) or ETHANOL SOLUTION

(ETHYL ALCOHOL SOLUTION)

C. Hazard Class(Transport): 3

D. Packing class: II

E. Marine poliutant: YES

F. EmS code

 \bigcirc Fire : F-E

○ Spill : S-D



15. regulatory information

A. Occupation Safety and Health Acts

O Working environment measurement materials : not applicable

O Exposure standard setting materials : Applicable (Ethyl Alcohol)

Managed Hazardous Materials
 Special medical examination material
 Manufacture Restriction Materials
 Need Permissioin Materials
 inot applicable
 not applicable

Need PSM MaterialsProduct, applicable (Flammable liquids)

B. Harmful chemical substance Management Acts

○ Toxic Materials
 ○ Emission Survey Materials
 ○ Accident Prepare Materials
 ○ Restriction Materials
 ○ Permission Materials
 ○ Prohibiton Materials
 ○ Inot applicable
 ○ Prohibiton Materials
 ○ Inot applicable
 ○ Prohibiton Materials
 ○ Inot applicable

O Related Law For Chemicals Registration, evaluation: Existing Chemicals (Ethanol, Water)

C. Hazardous Safety Control Acts : 4 Class Alcohols, 400 L

D. Waste Control Acts : This Product is Industrial Waste(except

for appointed Waste) in accordance

with Waste Control Acts

E. Other regulation and foreign regulation

O Persistent Organic Pollutants Control Acts : Not application

O EU Regulations

- Classification results : Flam. Liq. 2

- Hazard phases : H225

O US Regulations

- OSHA Regulations (29CFR1910.19) : Not application - CERCLA 103 Regulations (40CFR302.4) : Not application - EPCRA 302 Regulations (40CFR35.30) : Not application - EPCRA 304 Regulations (40CFR35.40) : Not application - EPCRA 313 Regulations (40CFR372.65) : Not application O Rotterdam Convention : Not application O Stockholm Convention : Not application O Montreal Protocol : Not application



16. other information

A. References : This MSDS is prepared in accordance with Article 41 of the Industrial Safety and Health Act and Article

2016-19 of the Ministry of Employment and Labor (standards on the provision of material safety data).

MSDS (KOSHA)

TOXNET, U.S. National Library of Medicine International Chemical Safety Cards(ICSC) ECS-ESIS(European chemical Substances

Information System), Chemical book, ECHA, HSDB

IUCLID Chemical Data Sheet, EC-ECB

NCIS, National Institute of Environmental Research Korea Information System for Chemical Safety

Management

B. Original preparation date : 2020, MAR. 11.

C. Revision number and revision date : 0 / 2020, MAR. 11.

D. Other No data : This information is based on current available DB to

protect workers' health, environment and safety.